

## TOAD A850T2

- **Thatcham Category 2 to 1 upgrade alarm system, providing perimeter and ultrasonic interior protection**
- **Switched from vehicle's existing OE remote controls**
- **Supplied with self powered siren, and red status LED**
- **Armed accessory output or timed output on arming**
- **Touch key override**



### Security Features -

- Switches securely from the vehicle's existing OE remote
- Perimeter protection circuit for boot and bonnet (negative input)
- Perimeter protection circuit for doors (positive or negative input)
- Ignition detection circuit
- Ultrasonic interior protection, manually adjustable
- Manual arm, using vehicle's existing OE remote or auto arm, which automatically arms the system 60 seconds after the last door is shut (the door will not lock at this point)
- Auto re-arm the system if a door is not opened within 60 seconds of disarming the alarm system the alarm will re-arm
- Last trigger identification via the dashboard LED, if the ignition is switched on upon disarming the system after an alarm condition has occurred
- Total trigger count memory for each individual circuit since system installed or the memory re-set
- Additional plug in single stage sensor socket (see optional accessories)
- Additional plug in dual stage sensor socket and siren pre-warn facility (see optional accessories)
- Secure data linked, self powered siren included

### Convenience Features -

- Armed output (negative 500mA max)
- Secure coded touch key override
- Silent arm and disarm (audible bleeps can be programmed back on, however this will breach current legislation)
- Sensors excludable using the supplied push button

### A850T Box Contents -

A850T alarm ECU  
Fixing screws  
A850T alarm installation wiring loom  
Secure data linked, self powered siren  
Siren lead with plug with bonnet switch wire  
Siren bracket and fixings  
Red status LED and loom  
Two ultrasonic heads  
Operating instructions  
Certificate of installation  
Two Toad window stickers  
Sheet of remaining foil stickers

### Optional Accessories -

#### Single Stage Sensors

- T-TS1 - Tilt sensor. Plug in sensor. Only for use in addition to the ultrasonic interior sensors  
AS610 - Single stage shock sensor. Plug in sensor. Only for use in addition to the ultrasonic interior sensors  
AS620 - Single zone microwave. Plug in sensor. Only for use in addition to the ultrasonic interior sensors

#### Dual Stage Sensors

- AS625 - Dual zone microwave. Plug in sensor. Only for use in addition to the ultrasonic interior sensors  
T2SS - Dual stage shock sensor. Plug in sensor. Only for use in addition to the ultrasonic interior sensors

**Other**

2012054 - RF pager  
PWC402 - 2 window closure module

**Quality and Approvals -**

Thatcham "Category 2 to 1" approved for passenger cars:

TU2-1104/0799

Thatcham "Category L2 to L1" approved for light commercial vehicles:

TUL-67/0801

EU 95/56 directive (security) and EU 95/54 directive (electrical) – "e" marked:

E1 A-00 0335

Life time warranty